

UNIVERSAL PROCESSORS

UNIVERSAL PROCESSOR

UP SERIES

The LaBounty Universal Processors are ideal for demolition, road and bridge reconstruction, and recycling operations. Up to 4 interchangeable jaws are offered per model, providing maximum versatility.

- 360° powered rotation – allows for efficient processing at virtually any angle.
- Time tested, spool type Speed Valve for fast cycle times.
- Two, large bore cylinders provide maximum power throughout the closing cycle and allow the jaws to align on material better as compared to single cylinder attachments.
- Reverse, mounted shrouded cylinders – The cylinder barrel moves back and forth, keeping the cylinder rods away from the material. The heavy-duty shrouds provide added protection.
- Multiple machine mount capability – Multi-machine head / lugs come standard with the UP SV series, allowing them to be mounted to other machines through the use of a pin and bushing kit (please call factory to verify mounting options).
- Swift Lock Tooth system is standard on most Concrete Pulverizer and Concrete Cracking Jaws.



	Excavator Wt 2nd member	Excavator Wt 3rd member	UP Weight w/ heaviest jaw set	Jaw Opening	Jaw Sets Available
UP 155V	N/A	33,000 LBS / 15 METRIC TONS	3,900 LBS / 1,770 METRIC TONS	14 IN / 360 CM	SHEAR
				25 IN / 640 CM	CONCRETE CRACKING
UP 205V	22,000 LBS / 10 METRIC TONS	44,000 LBS / 20 METRIC TONS	5,050 LBS / 2,040 METRIC TONS	18 IN / 460 CM	SHEAR
				24 IN / 610 CM	CONCRETE PULVERIZER
				29 IN / 740 CM	CONCRETE CRACKING
				11 IN / 280 CM	PLATE SHEAR
UP 305V	44,000 LBS / 20 METRIC TONS	66,000 LBS / 30 METRIC TONS	8,180 LBS / 3,720 METRIC TONS	25 IN / 640 CM	SHEAR
				32 IN / 810 CM	CONCRETE PULVERIZER
				41 IN / 1,040 CM	CONCRETE CRACKING
				14 IN / 360 CM	PLATE SHEAR
UP 755V	80,000 LBS / 30 METRIC TONS	135,000 LBS / 61 METRIC TONS	12,900 LBS / 5,860 METRIC TONS	33 IN / 840 CM	SHEAR
				40 IN / 1,020 CM	CONCRETE PULVERIZER
				49 IN / 1,250 CM	CONCRETE CRACKING